

MOVEMENT SENSOR

MOVEMENT SENSOR FOR DOWNDRAFT TABLE

Automatic start/stop device based on movement sensor, to be mounted on top of the back panel or backdraft panel of a downdraft table. After detecting any movement above the work grid, the automatic start/stop device activates the fan of the downdraft table to start running. When the work has stopped, the fan automatically switches off after a certain run-out period.

The cable, which is provided with a protective hose, is to be connected at the rear.



SPECIFICATIONS

■ Physical dimensions and properties	
Dimensions:	
• length	• 295 mm (11.61 in.)
• width	• 16,5 - 128,5 mm (0.65 - 5.06 in.)
• height	• 360,5 mm (14.19 in.)
Material	sheet metal
Colour	black RAL 9005 (gloss level 85%)
Weight (net)	3,1 kg (6.8 lbs)
Connection cable	2,3 m (7.5 ft)
■ Electrical data	
Power consumption	2,1 VA
Connection voltage	24 VAC
Start delay	2 seconds (adjustable)
Stop delay	60 seconds (adjustable)
Sensor type	passive infrared (PIR)
■ Product combinations	
DraftMax Ultra	downdraft table with automatic selfcleaning filter (with back panel or backdraft kit)
■ Scope of supply	
Bracket with movement sensor, 2,3 m of cable and plug - Bolt M6 (2) - Tie-wrap (3)	
■ Order information	
Article number	0040300050
Number/package	1
■ Shipping data	
Gross weight	3,8 kg (8.4 lbs)
Packing dimensions	450 x 380 x 160 mm (17.7 x 15.0 x 6.3 in.)
Harmonized Tariff Code	8421.39.2090
Country of origin	the Netherlands

APPROVALS/CERTIFICATES

	Directive 2011/65/EC (RoHS) valid as of 8 June 2011

FEATURES

Protective hose	
-----------------	--

Product type	Movement sensor
Article no.	0040300050
Product category	options and accessories
Version	020312/D

Always check the latest version on www.plymovent.com.