

SLICE® Battery/Utility Pack

Exothermic portable cutting packs with or without ignition source & oxygen supply



SLICE Utility Pack

Go anywhere and cut, burn, or pierce virtually any metallic, non-metallic or composite material with this exothermic cutting pack.

Comes with all the necessary equipment and cutting rods required to do cutting when combined with standard industrial grade oxygen to support the exothermic reaction and to remove the molten metal.

- New heavy-duty storage case to hold/store the equipment when not in use
- Improved torch handle & rubber shield to improve the operators grip and provide protection from molten spray when piercing
- Improved striker assembly that incorporates a slide mechanism that allows the operator to only expose a small portion of the ignition bar (copper) which increases the life of the striker copper bar

Battery Pack only:

- Improved battery ignition source with improved features over prior model
 - Faster recharging of a "dead" battery
 - Better visual "gas gauge" indicating battery condition
 - Over-charging safe guard

Visit esab.com for more information.

Industry

- Bridge Construction
- Industrial and General Fabrication
- Mining
- Repair and Maintenance
- Steel Erectors



SLICE Utility Pack



SLICE Battery Pack



SLICE Battery Ignition Source
(included in Battery Pack)

SLICE® Battery/Utility Pack

| Specifications | |
|---------------------------------------|--|
| Main Voltage (Input) | 120 V AC 60 Hz / 220 V AC 50 Hz (Battery Pack) |
| Output Voltage | 12 V DC |
| Type Of Battery | Seal lead acid |
| Recharge Time (fully drained battery) | 6 h |
| Exothermic Cutting Rods | 1/4 in. x 22 in. Uncoated – 25 pieces |
| Length Of Power Cable & Oxygen Hose | 3 m (10 ft.) |
| Power Cable AWG Size | #10 |
| Certification Mark (Standards) | CE |
| Dimensions L x W x H | 565.15 mm x 508 mm x 139.7 mm (22.25 in. x 20 in. x 5.5 in.) |
| Weight Battery Pack | 12.66 kg (27.9 lbs) |
| Weight Utility Pack | 9.48 kg (20.9lbs) |

| Ordering Information | |
|--|------------|
| SLICE Battery Pack CE – 220 V AC 60 Hz | 63991044CE |
| SLICE Utility Pack CE | 63991047CE |

| Options and Accessories | |
|--|--------------|
| SLICE Battery Ignition Source | 96-076-040 |
| Power Adapter w/ Europe Power Lead | 96-076-042 |
| SLICE Cutting Torch CE w/ #10 Power Cable (When Igniting w/ 12V Battery & Cutting w/o Power) | 03-003-012CE |
| SLICE Cutting Torch CE w/ #6 (When Igniting 12V Battery & Cutting w/o Power) | 03-003-011CE |
| SLICE Cutting Torch CE w/ #1 (Up to 200 A w/ Power) | 03-003-010CE |
| SLICE Striker Assembly | 72-012-010 |

| Cutting Rods | |
|--|----------|
| SLICE Exothermic Cutting Rods, Flux Coated, 1/4 x 22 - 100 Pcs | 42049003 |
| SLICE Exothermic Cutting Rods, Flux Coated, 1/4 x 22 - 25 Pcs | 42049002 |
| SLICE Exothermic Cutting Rods, Uncoated, 3/8 x 36 - 25 Pcs | 43049009 |
| SLICE Exothermic Cutting Rods, Uncoated, 3/8 x 18 - 50 Pcs | 43049007 |
| SLICE Exothermic Cutting Rods, Uncoated, 1/4 x 22 - 25 Pcs | 43049002 |
| SLICE Exothermic Cutting Rods, Uncoated, 1/4 x 44 - 25 Pcs | 43049005 |
| SLICE Exothermic Cutting Rods, Flux Coated, 3/8 x 18 - 50 Pcs | 42049005 |
| SLICE Exothermic Cutting Rods, Uncoated, 1/4 x 22 - 100 Pcs | 43049003 |



ESAB / esab.com

