

The RTQ40 fits where other drills can't — combining compact height with serious cutting power up to 40mm.

Built for structural steelwork and confined access, the RTQ40 is the lowest profile drill in the range. With a ratchet-feed system and powerful motor, it delivers clean broaching in overhead, inside-beam, or baseplate jobs other machines can't reach.



- Only 180mm tall — perfect for restricted or confined access
- 40mm cutting capacity with HSS or TCT cutters
- Ratchet feed enables controlled drilling in tight areas
- Weldon shank compatible for full tooling flexibility
- Built-in cooling system extends cutter life and precision
- Compact but powerful — ideal for fabrication and site work

TECHNICAL SPECIFICATIONS

MAX TCT CUTTER CAPACITY	40mm
MAX HSS CUTTER CAPACITY	36mm
TWIST DRILL CAPACITY	13mm
COUNTERSINKING	32mm
LENGTH	310mm
WIDTH	135mm
HEIGHT	180mm
STROKE	40mm
WEIGHT	10.8kg
MAGNET (L x W x H)	160x80x37mm
MAGNETIC FORCE	1200kg
MOTOR POWER	1050W
TOTAL POWER	1100W
SPEED RPM (No Load)	700RPM
SPINDLE	Quick change 19.05mm 3/4" Weldon arbor for all standard broaching cutters
COOLANT SYSTEM	Optional Extra
WARRANTY	2yr (When registered)



Part No	Contents
803084-110	RTQ40 Magnetic Drill 110v
803084-230	RTQ40 Magnetic Drill 230v

Supplied in **STAKIT®** Base 200 case with hex keys, restraint strap and ratchet.

