

WHEEL AMPERAGE CONTROL

Remote amperage controls provide welding power source contactor on-off, activate gas and/or water solenoids, and provide full range current output control. Handle style includes Velcro® straps where one size fits all handle diameters and retrofits easily on all makes of TIG torches.

- Returns to off automatically
- Insures electrode not “hot” when not in use
- Great for tack welding, short or long welds, and “bumping” technique
- Can be positioned closer to torch head for optimum torch control

**BUILT-IN SPRING FOR
AUTOMATIC RETURN
TO OFF**



WHEELED AMPERAGE CONTROL SELECTOR CHART CONTACT FACTORY FOR OTHER TIG MACHINES

MACHINE MAKE POTENTIOMETER RATING	PLUG CONFIG & PIN COUNT	CONTROL CABLE LENGTH	VELCRO® STRAPS
			ONE SIZE FITS ALL
MILLER ELECTRIC 1K Ohm	14 Pin Plug	15 ft. (4.6 m)	WACCV-1-1-M14
		28 ft. (8.5 m)	WACCV-1-2-M14
		53 ft. (16.2 m)	WACCV-1-3-M14
	5 Pin Plug	15 ft. (4.6 m)	WACCV-1-1-M5
		28 ft. (8.5 m)	WACCV-1-2-M5
		53 ft. (16.2 m)	WACCV-1-3-M5
	6 Pin Plug	15 ft. (4.6 m)	WACCV-1-1-M6
		28 ft. (8.5 m)	WACCV-1-2-M6
		53 ft. (16.2 m)	WACCV-1-3-M6
TWECO* 5K Ohm	14 Pin Plug	15 ft. (4.6 m)	WACCV-5-1-TD14
		28 ft. (8.5 m)	WACCV-5-2-TD14
		53 ft. (16.2 m)	WACCV-5-3-TD14
	8 Pin Plug	15 ft. (4.6 m)	WACCV-5-1-TD8
		28 ft. (8.5 m)	WACCV-5-2-TD8
		53 ft. (16.2 m)	WACCV-5-3-TD8
LINCOLN ELECTRIC 10K Ohm	14 Pin Plug	15 ft. (4.6 m)	WACCV-10-1-L14
		28 ft. (8.5 m)	WACCV-10-2-L14
		53 ft. (16.2 m)	WACCV-10-3-L14
	5 Pin Plug	15 ft. (4.6 m)	WACCV-10-1-L5
		28 ft. (8.5 m)	WACCV-10-2-L5
		53 ft. (16.2 m)	WACCV-10-3-L5
	6 Pin Plug	15 ft. (4.6 m)	WACCV-10-1-L6
		28 ft. (8.5 m)	WACCV-10-2-L6
		53 ft. (16.2 m)	WACCV-10-3-L6

*Tweco 186 AC/DC not available

Follow us: YouTube



Back To Table of Contents